

WPUST ŚCIEKOWY - ULICZNY

ŻELIWNY WPUST ULICZNY
ŚCIEKOWY D400
KOŁNIERZOWY Z KOSZEM

PIERŚCIEŃ UTRZYMUJĄCY
KRATĘ

ZAPRAWA CEMENTOWA 1:3

PIERŚCIEŃ ODCIĄŻAJĄCY

RURA BETONOWA Ø500
Z ODEJŚCIEM BOCZNYM
Ø200

RURA PVC 200mm

PO WMONTOWANIU
RURE OBETONOWAC

RURA BETONOWA Ø500

PŁYTA FUNDAMENTOWA
DENNA Ø750 h=120mm

Ø465

Ø500

Ø600

Ø750

h=1000

150

150

120

H całk

PŁYTA FUNDAMENTOWA
DENNA Ø750 h=120mm

The image contains two technical drawings of a hole with a hole-in-a-hole. The left drawing is a perspective view showing the hole in the hole at an angle. The right drawing is a front view showing the hole in the hole from the front. Both drawings include dimension lines and a label 'Ø960'.

Technical drawings of the 'Poziom krawężnik' (Flat curb) showing isometric, top, and side views with dimensions.

- Isometric View:** Shows the overall dimensions: length 810, width 650, and a curved front edge with a radius of 650.
- Top View:** Shows the width 650 and the internal width 255. The front edge is semi-circular with a radius of 325.
- Side View:** Shows the height 110, the top width 180, the total width 215, and the base width 540. The side profile is labeled 'Poziom krawężnik' and 'Poziom jezdní'.

umocnienie rowu brukiem na podsypce cem. - piask. 1:4 gr. 10cm

1. Ściany odlądowe izolować Abizolem "R"
2. Wylot zaopatrzyć w uchylną kratkę stalową ocynkowaną o rozstawie prętów 20 mm

Technical cross-section drawing of a drainage ditch. The drawing shows a concrete curb (Beton C12/15) with a height of 19 cm and a width of 25 cm. The ditch is filled with bedding (Podsypka z pospólki) and has a bottom width of 90 cm. The ditch is reinforced with a brick on a bedding of cement-sand (umocnienie rowu brukiem na podsypce cem. - piask. 1:4 gr. 10cm). The height of the ditch is 50 cm. The drawing also shows a slope of 1:1 and a requirement for $H1 \geq H2 + 0.1 \text{ m}$.

C - C

Technical drawing of a rectangular object with a circular feature. The object is shown in a perspective view. The dimensions are indicated by arrows and numbers: the total width is 26, the width of the circular feature is 20, and the width of the rectangular frame is 25. The height of the object is 25. A section line is shown below the object, indicating a cut through the center. The section line is labeled with the number 6.

